

Safety Data Sheet

Issue Date: 06-Jun-2018

Revision Date: 13-Jun-2018

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Duroseal Sealer Primer

Other means of identification

SDS # RES-004

UN/ID No UN1263

Recommended use of the chemical and restrictions on use

Recommended Use Restricted to professional users.

Details of the supplier of the safety data sheet

Supplier Address

Resurfacing.com
Melton Street, TX 77354: 832-934-2283

Emergency Telephone Number

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Gray liquid

Physical state Liquid

Odor Alcohol odor

Classification

| | |
|--|------------|
| Serious eye damage/eye irritation | Category 2 |
| Carcinogenicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 1 |
| Flammable Liquids | Category 3 |

Signal Word

Danger

Hazard statements

Causes serious eye irritation
Suspected of causing cancer
Causes damage to organs
Flammable liquid and vapor



Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not breathe dust/fume/gas/mist/vapors/spray
 Do not eat, drink or smoke when using this product
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Use explosion-proof equipment

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No. | Weight-% |
|----------------------|------------|----------|
| Ethyl Alcohol | 64-17-5 | 30-40 |
| Titanium(IV) Oxide | 13463-67-7 | 10-20 |
| Aluminum Silicate | 12141-46-7 | 5-10 |
| Isopropyl Alcohol | 67-63-0 | 5-10 |
| Uranium trioxide | 1344-58-7 | 1-5 |
| Mica | 12001-26-2 | 1-5 |
| Attapulgate Clay | 12174-11-7 | 1-5 |
| Barium Sulfate | 7727-43-7 | 1-5 |
| Methanol | 67-56-1 | 1-5 |
| 4-methylpentan-2-one | 108-10-1 | 0.1-0.5 |

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First Aid Measures

| | |
|-----------------------|---|
| General Advice | Provide this SDS to medical personnel for treatment. |
| Eye Contact | Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| Skin Contact | Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Call a poison center or doctor/physician if you feel unwell. Wash contaminated clothing before reuse. |

| | |
|-------------------|---|
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell. |
| Ingestion | If conscious give 2 glasses of water to dilute. Do not induce vomiting without medical advice. Call a poison center or doctor/physician if you feel unwell. |

Most important symptoms and effects

| | |
|-----------------|--|
| Symptoms | Causes serious eye irritation. Causes damage to organs. May be harmful in contact with skin. |
|-----------------|--|

Indication of any immediate medical attention and special treatment needed

| | |
|---------------------------|------------------------|
| Notes to Physician | Treat symptomatically. |
|---------------------------|------------------------|

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Carbon dioxide (CO₂). Dry chemical. Alcohol foam.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Flammable liquid and vapor. Container explosion may occur under fire conditions. Use water spray to keep containers cool.

Explosion Data

Sensitivity to Mechanical Impact Yes.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

| | |
|-----------------------------|---|
| Personal Precautions | Use personal protection recommended in Section 8. Evacuate personnel to safe areas. |
|-----------------------------|---|

Environmental precautions

| | |
|----------------------------------|---|
| Environmental precautions | Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. |
|----------------------------------|---|

Methods and material for containment and cleaning up

| | |
|--------------------------------|---|
| Methods for Containment | Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. |
| Methods for Clean-Up | Use only non-sparking tools. Take up with sand or other non-combustible absorbent material and place into containers for later disposal. For waste disposal, see section 13 of the SDS. |

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Use explosion proof equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Store in a cool, well-ventilated area, away from ignition sources and incompatible materials. Keep container tightly closed. Store locked up.

Incompatible Materials

Oxidizers. Acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|----------------------------------|---|--|---|
| Ethyl Alcohol 64-17-5 | STEL: 1000 ppm | TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³ | IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³ |
| Titanium(IV) Oxide 13463-67-7 | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust | IDLH: 5000 mg/m ³ |
| Aluminum Silicate 12141-46-7 | TWA: 1 mg/m ³ respirable particulate matter | - | - |
| Isopropyl Alcohol 67-63-0 | STEL: 400 ppm TWA: 200 ppm | TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³ | IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³ |
| Attapulgite Clay 12174-11-7 | TWA: 1 mg/m ³ respirable particulate matter | - | - |
| Uranium trioxide 1344-58-7 | STEL: 0.6 mg/m ³ U TWA: 0.2 mg/m ³ U | TWA: 0.25 mg/m ³ U (vacated) TWA: 0.2 mg/m ³ U (vacated) STEL: 0.6 mg/m ³ U | IDLH: 10 mg/m ³ U TWA: 0.2 mg/m ³ U STEL: 0.6 mg/m ³ U |
| Mica 12001-26-2 | TWA: 3 mg/m ³ respirable particulate matter | (vacated) TWA: 3 mg/m ³ respirable dust <1% Crystalline silica TWA: 20 mppcf <1% Crystalline silica | IDLH: 1500 mg/m ³ TWA: 3 mg/m ³ containing <1% Quartz respirable dust |
| Barium Sulfate 7727-43-7 | TWA: 5 mg/m ³ inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica | TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction | TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust |
| Methanol 67-56-1 | STEL: 250 ppm TWA: 200 ppm S* | TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S* | IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³ |

| | | | |
|----------------------------------|-----------------------------|--|---|
| 4-methylpentan-2-one 108-10-1 | STEL: 75 ppm TWA: 20 ppm | TWA: 100 ppm TWA: 410 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m ³ (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m ³ | IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³ |
|----------------------------------|-----------------------------|--|---|

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits. Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Goggles or a full-face shield. Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection If necessary, wear a MSHA/NIOSH-approved respirator. Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|-----------------------|-------------|-----------------------|----------------|
| Physical state | Liquid | Odor | Alcohol odor |
| Appearance | Gray liquid | Odor Threshold | Not determined |
| Color | Gray | | |

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|---------------------------------------|---------------------------|-------------------------|
| pH | 4.5 | |
| Melting point / freezing point | Not determined | |
| Boiling Point / Boiling Range | Est. 78.3 °C / 173 °F | |
| Flash Point | Approx. 23.8 °C / 75 °F | Setaflash |
| Evaporation Rate | Slower than butyl acetate | |
| Flammability (Solid, Gas) | Not determined | |
| Flammability Limit in Air | | |
| Upper Flammability Limit | Not determined | |
| Lower Flammability Limit | Not determined | |
| Vapor Pressure | Not determined | |
| Vapor Density | Lighter than air | (Air=1) |
| Relative Density | 1.2 | (Water = 1) |
| Water Solubility | Insoluble in water | |
| Solubility in other solvents | Not determined | |
| Partition Coefficient | Not determined | |
| Autoignition temperature | Not determined | |
| Decomposition Temperature | Not determined | |
| Kinematic Viscosity | Not determined | |
| Dynamic Viscosity | Not determined | |
| Explosive Properties | Not determined | |
| Oxidizing Properties | Not determined | |

Other Information

VOC Content 3.6 lbs/gal 430 g/L

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Keep out of reach of children.

Incompatible Materials

Oxidizers. Acids.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact

Causes serious eye irritation.

Skin Contact

May be harmful in contact with skin.

Inhalation

May produce symptoms of central nervous system depression, including headache, dizziness, nausea, loss of balance and drowsiness.

Ingestion

Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|----------------------------------|------------------------|---|---|
| Ethyl Alcohol 64-17-5 | = 7060 mg/kg (Rat) | - | = 124.7 mg/L (Rat) 4 h |
| Titanium(IV) Oxide 13463-67-7 | > 10000 mg/kg (Rat) | - | - |
| water 7732-18-5 | > 90 mL/kg (Rat) | - | - |
| Isopropyl Alcohol 67-63-0 | = 1870 mg/kg (Rat) | = 4059 mg/kg (Rabbit) | = 72600 mg/m ³ (Rat) 4 h |
| Barium Sulfate 7727-43-7 | = 307000 mg/kg (Rat) | - | - |
| Methanol 67-56-1 | = 6200 mg/kg (Rat) | = 15800 mg/kg (Rabbit) = 15840 mg/kg (Rabbit) | = 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h |
| 4-methylpentan-2-one 108-10-1 | = 2080 mg/kg (Rat) | = 3000 mg/kg (Rabbit) | = 8.2 mg/L (Rat) 4 h |

Information on physical, chemical and toxicological effects

Symptoms

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Carcinogenicity**

Suspected of causing cancer. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as an alcoholic beverage. Isopropyl Alcohol (IPA) is an IARC Monograph Group 3 chemical. IPA is a Group 1 when manufactured by the strong-acid process. Titanium dioxide is a possible carcinogen when it appears as a respirable dust.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|----------------------------------|-------|----------|-------|------|
| Ethyl Alcohol 64-17-5 | A3 | Group 1 | Known | X |
| Titanium(IV) Oxide 13463-67-7 | | Group 2B | | X |
| Isopropyl Alcohol 67-63-0 | | Group 3 | | X |
| 4-methylpentan-2-one 108-10-1 | A3 | Group 2B | | X |

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

Causes damage to organs.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (dermal) 2,615.10 mg/kg

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Toxic to aquatic life with long lasting effects.

Component Information

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|---------------------|---|--|--|
| Acetone 67-64-1 | | 4.74 - 6.33: 96 h Oncorhynchus mykiss mg/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50 | 10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50 |
| Toluene 108-88-3 | 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50 | 54: 96 h Oryzias latipes mg/L LC50 static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 12.6: 96 h Pimephales promelas mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static | 5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50 |

| | | | |
|----------------------------------|---|--|--|
| Methanol 67-56-1 | | 100: 96 h Pimephales promelas mg/L LC50 static 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 28200: 96 h Pimephales promelas mg/L LC50 flow-through 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through | |
| 4-methylpentan-2-one 108-10-1 | 400: 96 h Pseudokirchneriella subcapitata mg/L EC50 | 496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through | 170: 48 h Daphnia magna mg/L EC50 |
| Glycol Ether EB 111-76-2 | | 2950: 96 h Lepomis macrochirus mg/L LC50 1490: 96 h Lepomis macrochirus mg/L LC50 static | 1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50 |

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

| Chemical Name | Partition Coefficient |
|----------------------------------|-----------------------|
| Ethyl Alcohol 64-17-5 | -0.32 |
| Isopropyl Alcohol 67-63-0 | 0.05 |
| Methanol 67-56-1 | -0.77 |
| 4-methylpentan-2-one 108-10-1 | 1.19 |

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

| Chemical Name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|----------------------------------|------|-----------------------------------|------------------------|------------------------|
| Methanol 67-56-1 | | Included in waste stream: F039 | | U154 |
| 4-methylpentan-2-one 108-10-1 | | Included in waste stream: F039 | | U161 |

California Hazardous Waste Status

| Chemical Name | California Hazardous Waste Status |
|------------------------------|-----------------------------------|
| Ethyl Alcohol 64-17-5 | Toxic Ignitable |
| Isopropyl Alcohol 67-63-0 | Toxic Ignitable |
| Methanol 67-56-1 | Toxic Ignitable |

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1263
 Proper Shipping Name Paint
 Hazard Class 3
 Packing Group III

IATA

UN/ID No UN1263
 Proper Shipping Name Paint
 Hazard Class 3
 Packing Group III

IMDG

UN/ID No UN1263
 Proper Shipping Name Paint
 Hazard Class 3
 Packing Group III
 Marine Pollutant Yes

15. REGULATORY INFORMATION

International Inventories

| Chemical Name | TSCA | DSL/NDSL | EINECS/E LINCS | ENCS | IECSC | KECL | PICCS | AICS |
|----------------------|------|----------|-------------------|------|-------|------|-------|------|
| Ethyl Alcohol | X | X | X | X | X | X | X | X |
| Titanium(IV) Oxide | X | X | X | X | X | X | X | X |
| Aluminum Silicate | X | X | X | X | X | X | X | X |
| Isopropyl Alcohol | X | X | X | X | X | X | X | X |
| Attapulgite Clay | X | X | | | X | | X | X |
| Uranium trioxide | X | X | X | | | | | X |
| Mica | X | X | | | X | X | X | X |
| Barium Sulfate | X | X | X | X | X | X | X | X |
| Methanol | X | X | X | X | X | X | X | X |
| 4-methylpentan-2-one | X | X | X | X | X | X | X | X |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**CERCLA**

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|----------------------------------|--------------------------|----------------|--|
| Methanol 67-56-1 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |
| 4-methylpentan-2-one 108-10-1 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | CAS No. | Weight-% | SARA 313 - Threshold Values % |
|---------------------------------|-----------|----------|-------------------------------|
| Isopropyl Alcohol - 67-63-0 | 67-63-0 | 5-10 | 1.0 |
| Barium Sulfate - 7727-43-7 | 7727-43-7 | 1-5 | 1.0 |
| Methanol - 67-56-1 | 67-56-1 | 1-5 | 1.0 |
| 4-methylpentan-2-one - 108-10-1 | 108-10-1 | 0.1-0.5 | 1.0 |

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

| Chemical Name | California Proposition 65 |
|---------------------------------|-----------------------------|
| Ethyl Alcohol - 64-17-5 | Carcinogen Developmental |
| Titanium(IV) Oxide - 13463-67-7 | Carcinogen |
| Attapulgite Clay - 12174-11-7 | Carcinogen |
| Methanol - 67-56-1 | Developmental |
| 4-methylpentan-2-one - 108-10-1 | Carcinogen Developmental |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|----------------------------------|------------|---------------|--------------|
| Ethyl Alcohol 64-17-5 | X | X | X |
| Titanium(IV) Oxide 13463-67-7 | X | X | X |
| Isopropyl Alcohol 67-63-0 | X | X | X |
| Mica 12001-26-2 | X | X | X |
| Barium Sulfate 7727-43-7 | X | X | X |
| Methanol 67-56-1 | X | X | X |
| 4-methylpentan-2-one 108-10-1 | X | X | X |

16. OTHER INFORMATION

| | | | | |
|--------------------|---|---------------------------------------|---|--|
| <u>NFPA</u> | Health Hazards Not determined | Flammability Not determined | Instability Not determined | Special Hazards Not determined |
| <u>HMIS</u> | Health Hazards Not determined | Flammability Not determined | Physical hazards Not determined | Personal Protection Not determined |

Issue Date: 06-Jun-2018
Revision Date: 13-Jun-2018
Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet